

Manufacturers of Industrial & Decorative Coatings

# ALKYD UNDERCOAT

Pigmented Undercoat Alkyd Sealer

Pigmented Alkyd Undercoat with excellent wetting and penetration and good flow properties for brushing or spraying. Contains release agents for excellent sanding properties on unpainted gib, timber wood and plaster manufactured products and old painted surfaces.

## Typical Uses

- Gib Board
- Timber Trim
- Wood
- Plaster Board
- Masonry and Render
- Old trim paint
- Porous or powdering surfaces
- Wet Area Sealing
- Some composite boards

Specifications may be updated or revised at times . Please ensure through our representative that sheet being viewed is current . United Paints Limited P.O. Box 21 – 064 29 Empire Road Bridgend Christchurch Telephone : (03) 323 – 8743 Facsimile : (03) 323 – 7261

### **Physical Properties**

Vehicle Type Pigment Type Solvent Pot Life Gloss Level Volume Solids Colours Available Recommended Dry Film Thickness Theoretical Coverage Number of Coats Dry Time

Recoating Times

Abrasion Resistance Solvent & Chemical Resistance Wet Heat Resistance Durability Application

Basecoats

Thinning & Cleanup Pack Sizes

#### Alkyd **Titanium Dioxide Plus Extenders** Aromatics 18 Months Flat 44 % White (can tint) 35 microns per coat 11 - 12 sq m / per litre 2 coats Touch 2 hours Hard Overnight Minimum -90 minutes Maximum -unlimited Very Good Very Good. Very Good Excellent Can be applied by brushing rolling, speed brush or convention spray system. Straight onto wood or suitable prepared surface. Thin highly for excellent penetration . Mineral Turpentine 1 Litres & 4 Litres 20 litre drums.

### Performance

### Performance

- Good adhesion to difficult surfaces
- Single Pack
- Excellent Durability .
- Can be recoated indefinitely Stain blocking.
- Good wet area sealing.

Limitations

- Outdoor exposure in direct sunlight can cause yellowing of the paint film
- Aromatic odour needs to be managed in workplace exposure for populated environments.