

Manufacturers of Industrial & Decorative Coatings

United Paints Limited P.O. Box 21 064 29 Empire Road Bridgend Christchurch Telephone : (03) 323 8743 Facsimile : (03) 323 7261

SAFETY DATA SHEET UNIEPOXY ZINC PRIMER PART A

17th May 2023

1.0 Chemical Product and Company Identification

Trade Name:

UNIEPOXY ZINC PRIMER

Chemical Name:

ZINC DUST 2 PACK EPOXY PRIMER (PART A)

Manufacturers Name: Address: Telephone: Facsimile: United Paints 29 Empire Rd, Belfast, Christchurch (03) 323 8743 (03) 323 7261

Date of Issue:

Emergency Contact Numbers

National Poison & Hazardous Chemicals Information Centre United Paints Limited – Director (Mr M.Davies) 0800 POISON (03) 359 3528 Home 021 617 979 Mobile

2.0 Hazards Identification

HSNO APPROVAL CODE : HSR002662

HSNO CLASSIFICATIONS : 3.1C , 6.1E , 6.3A , 6.4A , 6.5B , 6.9 , 6.9B , 9.1A ,

GHS CLASSIFICATIONS : Aspiration Hazard Category 1 Chronic Aquatic Hazard Category 1 Eye Irritation Hazard Category 2A Flammable Liquid Category 3 Skin Irritation Category 2 Skin Sensitizer Category 1

3.0 Composition / Information on Ingredients

Ingredient	CAS No.	% By Weight
Zinc Dust	7440-66-6	80 - 95
Bisphenol A/ Epichlorohydrin resin	25036-25-3	2.5 - 10
Xylene	1330-20-7	1 - 3
N Butanol	71-36-3	1 - 3

4.0 First Aid Measures

4.1	Inhalation	Bring patient to fresh open air away from contaminated area. If not breathing or breathing difficult give oxygen. Apply CPR in cases of respiratory failure and seek medical assistance .
4.2	Skin Contact	Flush skin and hair with running water and soap if available . Remove contaminated clothing including footwear . Before reuse launder or replace .
4.3	Eye Contact	Flush with water lifting lids occasionally. Check for and remove any contact lenses . Seek medical attention .
4.4	Ingestion	Wash out mouth with water . Remove dentures if present . Do not induce vomiting. Keep patient warm and quiet. Seek medical attention immediately .
4.5	First Aid Facilities	Eyewash and normal washroom facilities and consumerables .
4.6	Notes to Doctor	Treat symptomatically . Aspiration is the main danger . Enforce bed rest and observe carefully . Prophylactic antibiotics useful . Observe for chemical pneumonitis . Gasto-intestinal absorption is significant with hydrocarbon solvents .For large ingestions cuffed endotracheal tube is recommended .

5.0 Fire Fighting Measures

5.1 Flashpoint 27°C

5.2 Flammability Limit 1.0 (Lower)

5.3 Extinguishing Media

Foam , carbon dioxide , dry chemical . DO NOT USE WATER JET

5.4 Hazardous Composition Products

May form toxic materials such as Carbon Monoxide and Carbon Dioxide.

5.5 Special Firefighting Procedures

Call Fire Service and tell them of location and nature of hazard . Water or Foam may cause frothing that can be violent, especially if sprayed into containers of hot burning liquid. Self contained breathing apparatus with full face piece should be used. Closed containers can be kept cool by water spray . Make sure of adequate supplies of extinguishing material available .

5.6 Unusual fire and Explosion Hazards

Vapours are heavier than air and may travel along ground and move by ventilation and ignite at a point far from the source. Sumps and drains should be checked for signs of accumulation .

Christchurch (03) 323 8743 Auckland (09) 265 0032 Palmerston North 021 682 151

5.7 Firefighting Personal Protective Equipment

Full protective clothing and self contained breathing apparatus . Water rinse shower available .

	6.0 Accidental	Release Measures
6.1	Minor Spills	Eliminate all sources of Ignition. Stop leak at source. Dyke area of spillage. Absorb with sand or other absorbent inert material.
6.2	Major Spills	Clear are from all public and personnel . Call fire service and advise on the nature of hazard . Ensure spill is contained however if spill enters waterways directly or through drains advise local environment protection authority .
6.2	Disposal	Destroy by controlled incineration by approved waste disposal group or use an authorised disposal area.
	7.0 Handling a	and Storage
7.1	Handling	Use in well ventilated area away from any source of ignition . Wear safety glasses , nitrile gloves , overalls , and approved cartridge respirator when spraying .
7.2	Storage	Store in a cool , authorised room away from any source of accidental ignition , or any oxidising agents . Do not store in any secondary packaging .

8.0 Exposure Controls / Personal Protection

8.1 Exposure Controls

<u>Ingredient</u>	<u>Standard</u>	Exposure Limits
Xylenes	NZ Workpace Exposure	TWA - 50 ppm TWA - 217 mg/m³
n- Butanol	NZ Workpace Exposure	Peak - 50 ppm Peak - 150 mg/m³
Zinc Powder / Dust	NZ Workpace Exposure	TWA - 10 mg/m³

8.2 Personal Protective Equipment

- Vapour Respirator
- X
- Splash Goggles
- Face Shield
- Gloves (Nitrile)



Synthetic Apron

Vapour Respirator

X Dust Respirator

9.0 Physical and Chemical Properties

9.1	Appearance	Very thick liquid
9.2	Odour	Slight Hydrocarbon
9.3	Boiling Point	110°- 140°C
9.4	Flash Point	27° C
9.5	Solubility in Water	None
9.6	Specific Gravity	3.1
9.7	ph Value	Not applicable
9.8	Vapour Pressure	Not Available
9.9	Vapour Density	2.8 average
0 10	Evanoration Pate	0.5(BA-1)

oration Rate	0.5 (BA=1)
ile Component	42.0 %
nability	Flammable Liquid
gnition Temp	Not Established
nability Limits	Lower 1.1 Upper 7.1
	le Component nability gnition Temp

Greyish flammable liquid with a mild solvent odour , which does not mix with water but will form a thin layer on water surface .

10.0 Stability and Reactivity

10.2 10.3	Chemical Stability Conditions to Avoid Materials to Avoid Hazardous Decomp	Stable under normal conditions Heat , Direct Sunlight , open flames or other ignition sources Strong oxidising agents Carbon monoxide , Carbon dioxide , fumes
	Products Hazardous Reactions Hazardous Polymerization	May react with incompatible materials Will not occur

11.0 Toxicological Information

11.1 Acute Toxicity

No toxicology data available for this product

11.2 Health Effects
SwallowedHarmful . Ingestion of this material may irritate the gastric
tract and cause nausea and vomiting .Eye Contact
Skin Contact
Chronic EffectsMay cause eye irritation, stinging, redness and blurred vision.
May cause itching, redness and irritation
Prolonged contact with skin may cause dermatitis .

12.0 Ecological Information

12.1 Ecotoxicity

No ecological data is available for this product .

Christchurch (03) 323 8743

Auckland (09) 265 0032

Palmerston North 021 682 151

12.2 Persistance / Not readily biodegradable . Degradability	
12.3 Mobility Air Water	Slow loss by evaporation Product spreads on surface of water .
12.4 Enviro Protection	Avoid contaminating waterways , soil , drains and sewers .
13.0 Disposal (Considerations
13.0 Disposal (13.1 Liquid	Considerations Dispose of waste through an approved facility .

14.0 Transport	Regulations
Labelling Required	FLAMMABLE LIQUID Red Diamond 3
UNDG	
U N Number	1263
Proper Shipping Name	Paint
D G Class	3
Hazchem Code	3 Y
Packing Group	III
IMDG (Maritime)	
IMDG Class	3
UN Number	1263
EMS Number	F-E , S-E
IMDG Subrisk	None
Packing Group	III
Special Provisions	163 223 944 955
Marine Pollutant	Not Determined
This material is classified a	as a clas 3 – Flammable Liquid according to NZS 5433 : 1999

This material is classified as a clas 3 – Flammable Liquid according to NZS 5433 : 1999 Transport of Dangerous Goods on Land .

This material must not be loaded in the same freight container or the same vehicle with :

Class 1	Exposives
Class 2.1	Flammable Gases
Class 2.3	Toxic Gases
Class 4.2	Spontaneously Combustible Substances
Class 5.1	Oxidising substances
Class 5.2	Organic Peroxides
Class 7	Radioactive materials unless specifically exempted

Must not be loaded in the same freight container , but can be in the same vehicle if separated hotizontally by a distance of 3 metes :

Class 4.3 Dangerous when wet substances .

Goods of packing group II or III may be loaded in the freight container or the same vehicle if transported in segregation devices with :

Class 4.2	Spontaneously Combustible Substances
Class 4.3	Dangerous when wet substances
Class 5.1	Oxidising substances
Class 5.2	Organic Peroxides

15.0	Regulatory	Information
Labelling		Class 3 , Flammable Liquid
Poisons Sc	hedule	S 4
Hazard Cat	egory	Harmful

16.0 Other Information

Revision Date	17 th May 2028
NZ Emergency Services	Telephone 111

NZ Poison Information Telephone 0800 POISON (0800 764 766)

The above information concerns only the above mentioned product and is not valid with any other product(s). The information is provided to the best of our knowledge, correctly and completely, in good faith but without warranty. It remains the user's responsibility to ensure the information is appropriate for their application of the product.