

Manufacturers of Industrial & Decorative Coatings

United Paints Limited P.O. Box 21 064 29 Empire Road Bridgend

Christchurch

Telephone: (03) 323 8743 Facsimile: (03) 323 7261

POLYURETHANE

Single Component Alkyd Polyurethane

Single component, urethane modified alkyd polyurethane clear for high performing clear coating.

Recommended for timber flooring, industrial maintenance, and topside marine coatings providing excellent durability, hardness and chemical resistance on various substrates.

Urethane modifying agent provides outstanding gloss and fast drying nature.

Typical Uses

- Timber Floors
- Outdoor Furniture
- Seed Crates
- Decorative Iron
- Machinery
- Scaffold Planking
- Spa Varnish
- Marine
- Concrete Protection
- Trim Varnish

Physical Properties

Vehicle Type Urethane modified Alkyd Polymer

Pigment Type Clear
Solvent Aromatic
Pot Life Not Applicable
Gloss Level High Gloss or Satin

Volume Solids 46 %

Colours Available Full colour range including clear

Recommended Dry Film Build 45 - 50 microns per coat
Theoretical Coverage 10 m2/lt @ 50 microns DFT

Number of Coats
Dry Time

Number of Coats
Dry Time

Number of Coats
Dry Time

Number of Coats
Two (Tack then Double head coat)
90 min @ 20 ° C

Hard Overnight

Recoating Times <u>Minimum</u> -Varies with temperature

Generally 3 hours for extra coat. <u>Maximum</u> -Depending on ambient temperature 6 - 8 hours maximum. Full cure may necessitate sanding.

Abrasion Resistance Excellent Solvent & Chemical Resistance Excellent.

Durability Excellent

Thinning & Cleanup Mineral Turps or Commercial Thinner Pack Sizes 1 Litre, 2 Litre, 4 Litre & 20 Litre

Surface preparation
Surface must be free from dirt, oil grease or moisture and suitably

prepared.

Performance

Performance

- Non yellowing Aliphatic / Acrylic
- Excellent long term durability.

Limitations

 Spray Application is preferred application but can be Brushed and Rolled with the correct thinner

Specifications may be updated or revised at times. Please ensure through our representative that sheet being viewed is current.