

Manufacturers of Industrial & Decorative Coatings

United Paints Limited P.O. Box 21 064 29 Empire Road Bridgend Christchurch Telephone : (03) 323 8743 Facsimile : (03) 323 7261

SAFETY DATA SHEET UNITHANE THINNER

1.0 Chemical Product and Company Identification

Trade Name:

UNITHANE THINNER

Chemical Name:

Paint Thinner

17th May 2023

Manufacturers Name: Address: Telephone: Facsimile: United Paints 29 Empire Rd, Belfast, Christchurch (03) 323 8743 (03) 323 7261

Date of Issue:

Emergency Contact Numbers

National Poison & Hazardous Chemicals Information Centre United Paints Limited – Director (Mr M.Davies)

(03) 474 0999 (03) 359 3528 Home 021 617 979 Mobile

2.0 Hazards Identification

HSNO APPROVAL CODE : HSR002662

HSNO CLASSIFICATIONS :

3.1B , 6.1D , 6.3A , 6.4A , 6.8B , 6.9B , 9.1B , 9.3C

Harmful, Flammable Liquid,

3.0 Composition / Information on Ingredients

Ingredient	% By Weight	TLV (TWA)	
Xylene	40 - 60 %	188 mg/m³	50ppm
High Boiling	40 - 60 %	590 mg/m□	200ppm

4.0 First Aid Measures

4.1	Inhalation	Bring patient to fresh open air. If breathing difficult give oxygen.
4.2	Skin Contact	Wash with soap and water. Remove and launder

Skin ContactWash with soap and water. Remove and launder
contaminated clothing before reuse.

4.3	Eye Contact	Flush with water lifting lids occasionally. Seek medical attention .
4.4	Ingestion	Do not induce vomiting. Keep patient warm and quiet. Seek medical attention immediately . Rinse mouth with water .
4.5	First Aid Facilities	Eyewash and normal washroom facilities and consumerables .
4.6	Notes to Doctor	Treat symptomatically . Aspiration is the main danger . Enforce bed rest and observe carefully . Prophylactic antibiotics useful . Observe for chemical pneumonitis . Gasto-intestinal absorption is significant with hydrocarbon solvents .For large ingestions cuffed endotracheal tube is recommended .

5.0 Fire Fighting Measures

- **5.1 Flashpoint 18**°C
- 5.2 Flammability Limit 1.2 (Lower)

5.3 Extinguishing Media

Foam , carbon dioxide , dry chemical .

5.4 Hazardous Composition Products

May form toxic materials such as Carbon Monoxide and Carbon Dioxide.

5.5 Special Firefighting Procedures

Call Fire Service and tell them of location and nature of hazard . Water or Foam may cause frothing that can be violent, especially if sprayed into containers of hot burning liquid. Self contained breathing apparatus with full face piece should be used. Closed containers can be kept cool by water spray .

Make sure of adequate supplies of extinguishing material available .

5.6 Unusual fire and Explosion Hazards

Vapours are heavier than air and may travel along ground and move by ventilation and ignite at a point far from the source. Sumps and drains should be checked for signs of accumulation .

5.7 Firefighting Personal Protective Equipment

Full protective clothing and self contained breathing apparatus . Water rinse shower available .

6.0 Accidental Release Measures

6.1 Minor Spills

Eliminate all sources of Ignition. Stop leak at source. Dyke area of spillage. Absorb with sand or other absorbent inert material.

Christchurch (03) 323 8743

Auckland (09) 265 0032

- 6.2 **Major Spills** Clear are from all public and personnel . Call fire service and advise on the nature of hazard . Ensure spill is contained however if spill enters waterways directly or through drains advise local environment protection authority.
- 6.2 Disposal Destroy by controlled incineration by approved waste disposal group or use an authorised disposal area.

7.0 Handling and Storage

- Use in well ventilated area away from any source of ignition. 7.1 Handling Wear safety glasses, nitrile gloves, overalls, and approved cartridge respirator when spraying .
- 7.2 Store in a cool, authorised room away from any source of Storage accidental ignition, or any oxidising agents.

8.0 **Exposure Controls / Personal Protection**

8.1 **Exposure Controls**

Contains > 30 % Aromatic Hydrocarbon solvent . Make sure level maintained below TLV of 50 ppm or provide personal protective equipment to suit .

8.2 **Personal Protective Equipment**

X Vapour Respirator Splash Goggles Face Shield X Gloves (Nitrile) X Synthetic Apron X Vapour Respirator **Dust Respirator**

Physical and Chemical Properties 9.0

Liquid

- 9.1 Appearance 9.2 Odour
- 9.3 **Boiling Point**
- 9.4 Flash Point
- Solubility in Water 9.5
- **Specific Gravity**
- 9.6 9.7
- ph Value
- 9.8 Vapour Pressure
- Vapour Density 9.9
- 9.10 Evaporation Rate 9.11 Volatile Component
- 9.12 Flammability
- 9.13 Autoignition Temp
- 9.14 Flammability Limits

Christchurch (03) 323 8743

138°- 142°C 28° C Negligible 0.84 Not applicable 60 mm Hg at 20°C 3.8 0.8 (BA=1) 100 % Flammable Liquid 520°C Lower 1.1 Upper 10

Hydrocarbon/Ester

Auckland (09) 265 0032

Coloured flammable liquid with a mild solvent odour , which does not mix with water but will form a thin layer on water surface .

10.0 Stability and Reactivity

- **10.1** Chemical Stability Stable under normal conditions 10.2 Conditions to Avoid Heat, Direct Sunlight, open flames or other ignition sources **10.3** Materials to Avoid Strong oxidising agents Carbon monoxide, Carbon dioxide, fumes 10.4 Hazardous Decomp Products **10.5 Hazardous Reactions** May react with incompatible materials 10.6 Hazardous Will not occur Polymerization **Toxicological Information** 11.0
- **11.1 Acute Toxicity** Dermal : Slightly Toxic Inhalation : Moderate Irritant
- 11.2 Health Effects
 Harmful . Ingestion of this material may irritate the gastric tract and cause nausea and vomiting .

 Eye Contact
 May cause eye irritation,stinging,redness and blurred vision.

 Skin Contact
 May cause itching,redness and irritation

 Chronic Effects
 Prolonged contact with skin may cause dermatitis .

12.0 Ecological Information

- **12.1 Ecotoxicity** No ecological data is available for this product .
- 12.2 Persistance / Not readily biodegradable . Degradability
- **12.3** Mobility Air
WaterSlow loss by evaporation
Product will mix partially with water .
- **12.4 Enviro Protection** Avoid contaminating waterways , soil , drains and sewers .

13.0 Disposal Considerations 13.1 Liquid Dispose of waste through an approved facility .

13.2 Containers Dispose of containers through metal recycler once empty containers have dried .

14.0 Transport Regulations

Labelling Required

FLAMMABLE LIQUID Red Diamond 3

Christchurch (03) 323 8743

Auckland (09) 265 0032

UNDG

	U N Number	1993
	Proper Shipping Name	Hazardous Substance n.o.s
	D G Class	3
	Hazchem Code	3 Y
	Packing Group	III
IMDG	(Maritime)	
	IMDG Class	3
	UN Number	1993
	EMS Number	F-E , S-E
	IMDG Subrisk	None
	Packing Group	III
	Special Provisions	163 223 944 955
	Marine Pollutant	Not Determined

This material is classified as a class 3 – Flammable Liquid according to NZS 5433 : 1999 Transport of Dangerous Goods on Land .

This material must not be loaded in the same freight container or the same vehicle with :

Class 1	Exposives
Class 2.1	Flammable Gases
Class 2.3	Toxic Gases
Class 4.2	Spontaneously Combustible Substances
Class 5.1	Oxidising substances
Class 5.2	Organic Peroxides
Class 7	Radioactive materials unless specifically exempted

Must not be loaded in the same freight container , but can be in the same vehicle if separated hotizontally by a distance of 3 metes :

Class 4.3 Dangerous when wet substances .

Goods of packing group II or III may be loaded in the freight container or the same vehicle if transported in segregation devices with :

Class 4.2	Spontaneously Combustible Substances
Class 4.3	Dangerous when wet substances
Class 5.1	Oxidising substances
Class 5.2	Organic Peroxides

15.0 Regulatory Information

Labelling

Class 3, Flammable Liquid

Poisons Schedule

S 4

Christchurch (03) 323 8743

Auckland (09) 265 0032

16.0 Other Information

Revision Date 17th May 2028

NZ Emergency Services Telephone 111

NZ Poison Information Telephone 0800 POISON (0800 764 766)

The above information concerns only the above mentioned product and is not valid with any other product(s). The information is provided to the best of our knowledge, correctly and completely, in good faith but without warranty. It remains the user's responsibility to ensure the information is appropriate for their application of the product.