



United Paints Limited
P.O. Box 21 064
29 Empire Road
Bridgend
Christchurch
Telephone : (03) 323 8743
Facsimile : (03) 323 7261

Manufacturers of Industrial & Decorative Coatings

Hi Fill Undercoat & Sealer

Waterbased Sealer & Undercoat

Hi Fill Undercoat & Sealer is a waterbased latex product designed to be fast drying and suitable for top coating with most decorative topcoats. It has good opacity and easy application properties.

Typical Uses

- Concrete Blocks & Brickwork
- Paper faced Plasterboard
- Particle & Fibreboard
- Cement Plasters
- Wallboards
- Furniture
- Customwood

Specifications may be updated or revised at times . Please ensure through our representative that sheet being viewed is current .

Physical Properties

Vehicle Type	Latex Emulsion
Pigment Type	Titanium Dioxide
Solvent	Water
Pot Life	Not Applicable
Gloss Level	Low Sheen
Volume Solids	60 -65 %
Colours Available	White
Recommended Dry Film Build	30 microns per coat
Theoretical Coverage	Varies according to porosity of surface – up to 13 m2 / lit 30 microns Dry Film Build
Number of Coats	One
Dry Time	40 min @ 20°C
Recoating Times	<u>Minimum</u> – Varies with Temperature and application, usually 2 hours.
Abrasion Resistance	Very Good
Solvent & Chemical Resistance	Very Good
Toxicity	Non Toxic
Heat Resistance	Thermoplastic
Durability	Excellent when topcoated with recommended topcoat
Thinning & Cleanup	Water Clean up.
Pack Sizes	4 Litres, 10 Litres & 20 Litres

Performance

- | | |
|-------------|--|
| Performance | <ul style="list-style-type: none"> • Excellent Substrate & Intercoat adhesion. • High mould & mildew resistance • Can be applied by Brush, Roller or Airless Spray • Can be applied over most surfaces or previous coatings. • High Build Potential |
| Limitations | <ul style="list-style-type: none"> • Do not apply when ambient temperature is below 10°C. • Should not be used on contacting sashes or doors. |