



**United Paints Limited**  
**P.O. Box 21 – 064**  
**29 Empire Road**  
**Bridgend**  
**Christchurch**  
**Telephone : (03) 323 – 8743**  
**Facsimile : (03) 323 – 7261**

Manufacturers of Industrial & Decorative Coatings

**POLYPROPYLENE  
PRIMER**

Low Solids Adhesion  
Promoting Clear

Blended Polyolfin resin in solution with an aromatic hydrocarbon solvent for improving the adhesion of subsequent coats to most plastics and some alloys .

**Typical Uses**

- Brush Handles
- Bumper Repairs
- Furniture Coating
- Automotive Components
- Broom Handles
- Ornamental Plastic Work
- Plastic Sculpture
- Model Craft
- Display Figurines
- Picture Framing

Specifications may be updated or revised at times . Please ensure through our representative that sheet being viewed is current .

**Physical Properties**

Vehicle Type	Blended Polyolfin
Pigment Type	Unpigmented
Solvent	Aromatic
Pot Life	2 Years
Gloss Level	Low Sheen
Volume Solids	5 %
Colours Available	Clear only
Recommended Dry Film Thickness	6 micron
Theoretical Coverage	12 sq. / m per litre
Number of Coats	One
Dry Time	Touch 10 mins Hard 15 mins
Recoating Times	<u>Minimum</u> -2 hours <u>Maximum</u> -6 weeks
Abrasion Resistance	Good
Solvent & Chemical Resistance	Very Good.
Heat Resistance	Average
Durability	Topcoated Excellent
Application	Supplied ready to use from drum . Can be spray applied or dipped without reducing .
Thinning & Cleanup	Dual Purpose Solvent
Pack Sizes	4 Litres & 20 Litres 200 lt Drums

**Performance**

Performance	<ul style="list-style-type: none"> <li>• Ties to most plastics</li> <li>• Single Pack</li> <li>• Excellent Plastic Adhesion .</li> <li>• Can be overcoated with lacquers alkyds , vinyls and some urethanes</li> <li>• One application usually enough .</li> </ul>
Limitations	<ul style="list-style-type: none"> <li>• Dipping Application is preferred application for maximum efficiency</li> <li>• Product is designed for adhesion to most plastics . ABS and some other rigid plastics may not obtain desired adhesion profile .</li> <li>• Must be topcoated .</li> </ul>