



United Paints Limited
 P.O. Box 21 – 064
 29 Empire Road
 Bridgend
 Christchurch

Telephone : (03) 323 – 8743
 Facsimile : (03) 323 – 7261

Manufacturers of Industrial & Decorative Coatings

UNILAC

Clear Gloss Nitrocellulose Lacquer

Modified Nitrocellulose Lacquer
 Clear formulated with low flash point and good flow properties for spraying or dipping . Contains waxes for excellent abrasion resistance on furniture , and other wood and plastic manufactured products .

Typical Uses

- Furniture
- Cabinetry
- Shelving
- Displays
- Picture Frames
- Paint Brush Handles
- Brooms
- Brass Protection
- Wooden Ornamental Crafts
- MDF Sealing

Specifications may be updated or revised at times . Please ensure through our representative that sheet being viewed is current .

Physical Properties

Vehicle Type	Modified Nitrocellulose
Pigment Type	Unpigmented
Solvent	Ketones and Aromatics
Pot Life	18 Months
Gloss Level	100 % Gloss
Volume Solids	28 %
Colours Available	Clear
Recommended Dry Film Thickness	20 microns per coat
Theoretical Coverage	5 - 6 sq m / per litre
Number of Coats	3 - 4 coats
Dry Time	Touch 20 minutes Hard 2 hours
Recoating Times	<u>Minimum</u> -30 minutes <u>Maximum</u> -unlimited
Abrasion Resistance	Excellent
Solvent & Chemical Resistance	Very Good.
Heat Resistance	Very Good
Durability	Excellent
Application	Can be applied by dipping conventional spray or suitable pressure pot system .
Basecoats	Straight onto wood or suitable sanding sealer or overcoating pigmented lacquers .
Thinning & Cleanup	Lacquer Thinner
Pack Sizes	4 Litres & 20 Litres 200 litre drums .

Performance

Performance	<ul style="list-style-type: none"> • Scratch and Mar Resistant • Single Pack • Excellent Durability . • Can be recoated indefinitely over itself . • Good Yellowing resistance .
Limitations	<ul style="list-style-type: none"> • Outdoor exposure in direct sunlight can accelerate deterioration of the paint film • High moisture levels at time of application can result in blooming or chilling . Use appropriate thinner for each environment .