



Manufacturers of Industrial & Decorative Coatings

United Paints Limited
P.O. Box 21 064
29 Empire Road
Bridgend
Christchurch
Telephone : (03) 323 8743
Facsimile : (03) 323 7261

SAFETY DATA SHEET
UNIEPOXY ALUMINIUM MASTIC PART A

1.0 Chemical Product and Company Identification

Trade Name: UNIEPOXY ALUMINIUM MASTIC
Chemical Name: ALUMINIUM MASTIC COATING (PART A)
Manufacturers Name: United Paints
Address: 29 Empire Rd, Belfast, Christchurch
Telephone: (03) 323 8743
Facsimile: (03) 323 7261
Date of Issue: 26 JULY 2013

Emergency Contact Numbers

National Poison & Hazardous Chemicals Information Centre 0800 POISON
United Paints Limited – Director (Mr M.Davies) (03) 359 3528 Home
021 617 979 Mobile

2.0 Hazards Identification

HSNO APPROVAL CODE : HSR002662

HSNO CLASSIFICATIONS : 3.1B , 6.1E , 6.3A , 6.4A , 6.5B , 6.9 ,
6.9B , 9.1A ,

GHS CLASSIFICATIONS : Aspiration Hazard Category 1
Chronic Aquatic Hazard Category 1
Eye Irritation Hazard Category 2A
Flammable Liquid Category 3
Skin Irritation Category 2
Skin Sensitizer Category 1

3.0 Composition / Information on Ingredients

Ingredient	CAS No.	% By Weight
Bisphenol A/ Epichlorohydrin resin	25036-25-3	2.5 - 10
Xylene	1330-20-7	1 - 3
N Butanol	71-36-3	1 - 3

Christchurch
(03) 323 8743

Auckland
(09) 265 0032

Palmerston North
021 682 151

4.0 First Aid Measures

- 4.1 Inhalation** Bring patient to fresh open air away from contaminated area. If not breathing or breathing difficult give oxygen. Apply CPR in cases of respiratory failure and seek medical assistance .
- 4.2 Skin Contact** Flush skin and hair with running water and soap if available . Remove contaminated clothing including footwear . Before reuse launder or replace .
- 4.3 Eye Contact** Flush with water lifting lids occasionally. Check for and remove any contact lenses . Seek medical attention .
- 4.4 Ingestion** Wash out mouth with water . Remove dentures if present . Do not induce vomiting. Keep patient warm and quiet. Seek medical attention immediately .
- 4.5 First Aid Facilities** Eyewash and normal washroom facilities and consumerables .
- 4.6 Notes to Doctor** Treat symptomatically . Aspiration is the main danger . Enforce bed rest and observe carefully . Prophylactic antibiotics useful . Observe for chemical pneumonitis . Gasto-intestinal absorption is significant with hydrocarbon solvents .For large ingestions cuffed endotracheal tube is recommended .

5.0 Fire Fighting Measures

- 5.1 Flashpoint** 27°C
- 5.2 Flammability Limit** 1.0 (Lower)
- 5.3 Extinguishing Media**
Foam , carbon dioxide , dry chemical .
DO NOT USE WATER JET
- 5.4 Hazardous Composition Products**
May form toxic materials such as Carbon Monoxide and Carbon Dioxide.
- 5.5 Special Firefighting Procedures**
Call Fire Service and tell them of location and nature of hazard .
Water or Foam may cause frothing that can be violent, especially if sprayed into containers of hot burning liquid. Self contained breathing apparatus with full face piece should be used.
Closed containers can be kept cool by water spray .
Make sure of adequate supplies of extinguishing material available .
- 5.6 Unusual fire and Explosion Hazards**
Vapours are heavier than air and may travel along ground and move by ventilation and ignite at a point far from the source. Sumps and drains should be checked for signs of accumulation .

5.7 Firefighting Personal Protective Equipment

Full protective clothing and self contained breathing apparatus .
Water rinse shower available .

6.0 Accidental Release Measures

- 6.1 Minor Spills** Eliminate all sources of Ignition. Stop leak at source. Dyke area of spillage. Absorb with sand or other absorbent inert material.
- 6.2 Major Spills** Clear are from all public and personnel .
Call fire service and advise on the nature of hazard .
Ensure spill is contained however if spill enters waterways directly or through drains advise local environment protection authority .
- 6.2 Disposal** Destroy by controlled incineration by approved waste disposal group or use an authorised disposal area.

7.0 Handling and Storage

- 7.1 Handling** Use in well ventilated area away from any source of ignition .
Wear safety glasses , nitrile gloves , overalls , and approved cartridge respirator when spraying .
- 7.2 Storage** Store in a cool , authorised room away from any source of accidental ignition , or any oxidising agents . Do not store in any secondary packaging .

8.0 Exposure Controls / Personal Protection

8.1 Exposure Controls

<u>Ingredient</u>	<u>Standard</u>	<u>Exposure Limits</u>
Xylenes	NZ Workplace Exposure	TWA - 50 ppm TWA - 217 mg/m ³
n- Butanol	NZ Workplace Exposure	Peak - 50 ppm Peak - 150 mg/m ³
Zinc Powder / Dust	NZ Workplace Exposure	TWA - 10 mg/m ³

8.2 Personal Protective Equipment

- Vapour Respirator
- Splash Goggles
- Face Shield
- Gloves (Nitrile)

- Synthetic Apron
- Vapour Respirator
- Dust Respirator

9.0 Physical and Chemical Properties

9.1 Appearance	Very thick liquid
9.2 Odour	Slight Hydrocarbon
9.3 Boiling Point	110°- 140°C
9.4 Flash Point	27° C
9.5 Solubility in Water	None
9.6 Specific Gravity	3.1
9.7 pH Value	Not applicable
9.8 Vapour Pressure	Not Available
9.9 Vapour Density	2.8 average
9.10 Evaporation Rate	0.5 (BA=1)
9.11 Volatile Component	42.0 %
9.12 Flammability	Flammable Liquid
9.13 Autoignition Temp	Not Established
9.14 Flammability Limits	Lower 1.1 Upper 7.1

Greyish flammable liquid with a mild solvent odour , which does not mix with water but will form a thin layer on water surface .

10.0 Stability and Reactivity

10.1 Chemical Stability	Stable under normal conditions
10.2 Conditions to Avoid	Heat , Direct Sunlight , open flames or other ignition sources
10.3 Materials to Avoid	Strong oxidising agents
10.4 Hazardous Decomp Products	Carbon monoxide , Carbon dioxide , fumes
10.5 Hazardous Reactions	May react with incompatible materials
10.6 Hazardous Polymerization	Will not occur

11.0 Toxicological Information

11.1 Acute Toxicity	No toxicology data available for this product
11.2 Health Effects Swallowed	Harmful . Ingestion of this material may irritate the gastric tract and cause nausea and vomiting .
Eye Contact	May cause eye irritation, stinging, redness and blurred vision.
Skin Contact	May cause itching, redness and irritation
Chronic Effects	Prolonged contact with skin may cause dermatitis .

12.0 Ecological Information

12.1 Ecotoxicity	No ecological data is available for this product .
-------------------------	--

12.2 Persistence / Degradability	Not readily biodegradable .
12.3 Mobility Air Water	Slow loss by evaporation Product spreads on surface of water .
12.4 Enviro Protection	Avoid contaminating waterways , soil , drains and sewers .

13.0 Disposal Considerations

13.1 Liquid	Dispose of waste through an approved facility .
13.2 Containers	Dispose of containers through metal recycler once empty containers have dried and hardened .

14.0 Transport Regulations

Labelling Required FLAMMABLE LIQUID
Red Diamond 3

UNDG

U N Number	1263
Proper Shipping Name	Paint
D G Class	3
Hazchem Code	3 Y
Packing Group	III

IMDG (Maritime)

IMDG Class	3
UN Number	1263
EMS Number	F-E , S-E
IMDG Subrisk	None
Packing Group	III
Special Provisions	163 223 944 955
Marine Pollutant	Not Determined

This material is classified as a clas 3 – Flammable Liquid according to NZS 5433 : 1999 Transport of Dangerous Goods on Land .

This material must not be loaded in the same freight container or the same vehicle with :

Class 1	Explosives
Class 2.1	Flammable Gases
Class 2.3	Toxic Gases
Class 4.2	Spontaneously Combustible Substances
Class 5.1	Oxidising substances
Class 5.2	Organic Peroxides
Class 7	Radioactive materials unless specifically exempted

Must not be loaded in the same freight container , but can be in the same vehicle if separated horizontally by a distance of 3 metres :

Class 4.3 Dangerous when wet substances .

Goods of packing group II or III may be loaded in the freight container or the same vehicle if transported in segregation devices with :

Class 4.2	Spontaneously Combustible Substances
Class 4.3	Dangerous when wet substances
Class 5.1	Oxidising substances
Class 5.2	Organic Peroxides

15.0 Regulatory Information

Labelling	Class 3 , Flammable Liquid
Poisons Schedule	S 4
Hazard Category	Harmful

16.0 Other Information

Revision Date	20 JULY 2013
NZ Emergency Services	Telephone 111
NZ Poison Information	Telephone 0800 POISON (0800 764 766)

The above information concerns only the above mentioned product and is not valid with any other product(s). The information is provided to the best of our knowledge, correctly and completely, in good faith but without warranty. It remains the user's responsibility to ensure the information is appropriate for their application of the product.